

hyperref package options

Sebastian Rahtz et. al.

September 4th 2006

a4paper	use A4 paper	
a5paper	use A5 paper	
anchorcolor	set color of anchors	black
b5paper	use B5 paper	
backref	do bibliographical back references	false
baseurl	set base URL for document	<i>empty</i>
bookmarks	make bookmarks	true
bookmarksnumbered	put section numbers in bookmarks	false
bookmarksopen	open up bookmark tree	false
bookmarksopenlevel	level to which bookmarks are open	\maxdimen
bookmarkstype	to specify which ‘toc’ file to mimic	toc
breaklinks	allow links to break over lines	false
citebordercolor	color of border around cites	0 1 0
citecolor	color of citation links	green
colorlinks	color links	false
		true (tex4ht, dviwindo)
debug	provide details of anchors defined same as verbose	false
draft	do not do any hyper linking	false
dvipdf	use dvipdf backend	
dvipdfm	use dvipdfm backend	
dvipdfmx	use dvipdfmx backend	
dvips	use dvips backend	
dvipsone	use dvipsone backend	
dviwindo	use dviwindo backend	
encap	to set encap character for hyperindex	
executivepaper	use executivepaper	
extension	suffix of linked files	dvi
filebordercolor	color of border around file links	0 .5 .5
filecolor	color of file links	cyan
final	opposite of option draft	true
frenchlinks	use small caps instead of color for links	false
hyperfigures	make figures hyper links	false
hyperfootnotes	set up hyperlinked footnotes	true
hyperindex	set up hyperlinked indices	true
hypertex	use HyperTeX backend	
hypertextnames	use guessable names for links	true
implicit	redefine L ^A T _E X internals	true
latex2html	use L ^A T _E X2HTML backend	
legalpaper	use legalpaper	
letterpaper	use letterpaper	
linkbordercolor	color of border around links	1 0 0
linkcolor	color of links	red

linktocpage	make page number, not text, be link on TOC, LOF and LOT	false
menubordercolor	color of border around menu links	1 0 0
menucolor	color for menu links	red
naturalnames	use L ^A T _E X-computed names for links	false
nesting	allow nesting of links	false
pageanchor	put an anchor on every page	true
pagebackref	backreference by page number	false
pdfauthor	text for PDF Author field	<i>empty</i>
pdfborder	width of PDF link border	0 0 1 0 0 0 (colorlinks)
pdfcenterwindow	position the document window center of the screen	false
pdfcreator	text for PDF Creator field	LaTeX with hyperref package
pdfdirection	direction setting	<i>empty</i>
pdfdisplaydoctitle	display document title instead of file name in title bar	false
pdfduplex	paper handling option for print dialog	<i>empty</i>
pdfffitwindow	resize document window to fit document size	false
pdfhighlight	set highlighting of PDF links	/I
pdfkeywords	text for PDF Keywords field	<i>empty</i>
pdflang	PDF language identifier (RFC 3066)	<i>empty</i>
pdfmenubar	make PDF viewer's menu bar visible	true
pdfnewwindow	make links that open another PDF file start a new window	false
pdfnonfullscreenpagemode	page mode setting on exiting full-screen mode	<i>empty</i>
pdfnumcopies	number of printed copies	<i>empty</i>
pdfpagelayout	set layout of PDF pages	<i>empty</i>
pdfpagemode	set default mode of PDF display	<i>empty</i>
pdfpagelabels	set PDF page labels	false
pdfpagescrop	set crop size of PDF document	<i>empty</i>
pdfpagetransition	set PDF page transition style	<i>empty</i>
pdfpicktrackbypdfsize	set option for print dialog	<i>empty</i>
pdfprintarea	set /PrintArea of viewer preferences	<i>empty</i>
pdfprintclip	set /PrintClip of viewer preferences	<i>empty</i>
pdfprintpagerange	set /PrintPageRange of viewer preferences	<i>empty</i>
pdfprintscaling	page scaling option for print dialog	<i>empty</i>
pdfproducer	text for PDF Producer field	<i>empty</i>
pdfstartpage	page at which PDF document opens	1
pdfstartview	starting view of PDF document	/Fit
pdfsubject	text for PDF Subject field	<i>empty</i>
pdftex	use pdfT _E X backend	
pdftitle	text for PDF Title field	<i>empty</i>
pdftoolbar	make PDF toolbar visible	true
pdfview	PDF 'view' when on link traversal	<i>empty</i>
pdfviewarea	set /ViewArea of viewer preferences	<i>empty</i>
pdfviewclip	set /ViewClip of viewer preferences	<i>empty</i>
pdfwindowui	make PDF user interface elements visible	true
plainpages	do page number anchors as plain arabic	true
ps2pdf	use ps2pdf backend	
raiselinks	raise up links (for HyperTeX backend)	false
runbordercolor	color of border around 'run' links	0 .7 .7
runcolor	color of 'run' links	filecolor

setpagesize	set page size by special driver commands	true
tex4ht	use T _E X4ht backend	
textures	use Textures backend	
unicode	Unicode encoded pdf strings	
urlbordercolor	color of border around URL links	0 1 1
urlcolor	color of URL links	magenta
verbose	be chatty	false
vtex	use V _T E _X backend	
vtexpdfmark	use backend for V _T E _X in PDF/PS mode (pdf-mark specials)	
xetex	use XeTeX backend	
