


PSTricks

pst-fit

Curve fitting; v.0.01


November 1, 2012



Package author(s):
Buddy Ledger


Contents

1	Fit of Linear Function	3
2	Fit of Power Function	4
3	Fit of exp Function	5
4	Fit of Log10/Loge Functions	6
5	Fit of Recip	7
6	Fit of Kings Law data	8
7	Fit of Guassian	9
8	Fit of 4th Order Polynomial	10
9	LinetoXAxis respects scalepoints.	11
10	Prepare Points Modification	12
11	PrintCoor Demo	13
12	List of all optional arguments for pst-fit	14
	References	15

1 Fit of Linear Function

```
1 \begin{psgraph}[arrows=->,Dy=2](0,0)(0,0)(10,22){4.5in}{4.5in}
2 \listplot[decimals=2,EqPos=3 15,plotstyle=GLLSR,linestyle=dashed]{\Linear}
3 \listplot[plotstyle=dots,linecolor=red,dotscale=2,dotstyle=x]{\Linear}
4 \end{psgraph}
```

2 Fit of Power Function




```

1 \begin{psgraph}[arrows=->,Dy=100](0,0)(0,0)(10,1000){4.5in}{4.5in}
2 \listplot[decimals=2,EqPos=1 800,linestyle=dashed,plotstyle=GLLSR,PowerFit]{\
   Power}
3 \listplot[plotstyle=dots,linicolor=red,dotscale=2,dotstyle=x]{\Power}
4 \listplot[EqPos=5 4,plotstyle=GLLSR,linicolor=blue,CustomFit,CheckZeroX,
   CheckZeroY,FYtrans=log,RYtrans=10 exch exp,FXtrans=log]{\Power}
5 \end{psgraph}

```

3 Fit of exp Function




```

1 \begin{psgraph}[arrows=->,Dx=1,Dy=1000,xsubticks=1,ysubticks=1](0,0)(0,0)
  (10,10000){4.5in}{4.5in}
2 \listplot[PstDebug=1,decimals=2,EqPos=4 2000,MaPos=5 7000,plotstyle=GLLSR,
  ExpFit]{\Exp}
3 \listplot[plotstyle=dots]{\Exp}
4 \end{psgraph}

```

4 Fit of Log10/Loge Functions




```

1 \begin{psgraph}[arrows=->,Dx=1,Dy=2,xsubticks=1,ysubticks=1](0,0)(0,0)(10,50)
   {4.5in}{4.5in}
2 \listplot[decimals=2,EqPos=5 10,plotstyle=GLLSR,LogTFit]{\Logt}
3 \listplot[decimals=2,plotstyle=dots]{\Logt}
4 \listplot[decimals=2,EqPos=5 28,plotstyle=GLLSR,LogEFit]{\Loge}
5 \listplot[decimals=2,plotstyle=dots]{\Loge}
6 %\listplot[EqPos=5 4,plotstyle=GLLSR,CustomFit,CheckZeroX=true,CheckZeroY=true
   ,FYtrans=Yint dup mul sub %log,RYtrans=10 exch exp Yint dup mul add,FXtrans=
   log]{\Linear}
7 \end{psgraph}

```

5 Fit of Recip




```

1 \begin{psgraph}[arrows=<->,Dx=1,Dy=10,xsubticks=1,ysubticks=1](0,0)(0,0)
   (10,100){4.5in}{4.5in}
2 \listplot[decimals=2,EqPos=5 2,plotstyle=GLLSR,RecipFit]{\Recip}
3 \listplot[plotstyle=dots]{\Recip}
4 \end{psgraph}

```

6 Fit of Kings Law data




```

1 \begin{psgraph}[arrows=->,Dx=1,Dy=1,xsubticks=1,ysubticks=1](0,0)(10,20)
   {4.5in}{4.5in}
2 \pstScalePoints(1,1){}{dup mul}
3 \listplot[decimals=2,EqPos=5 2,plotstyle=GLLSR,PowerFit,Yint=5]{\King}
4 \listplot[plotstyle=dots]{\King}
5 \pstScalePoints(1,1){}{}
6 \end{psgraph}

```


7 Fit of Gaussian




```

1 \begin{psgraph}[arrows=->,Dx=1,Dy=0.1,xsubticks=1,ysubticks=1](0,0)(-10,0)
   (10,1){4.5in}{4.5in}
2 \listplot[plotstyle=dots]{\Gauss}
3 \listplot[decimals=2,EqPos=5 0.4,plotstyle=GLLSR,GaussFit,plotpoints=400]{\
   Gauss}
4 \end{psgraph}

```

8 Fit of 4th Order Polynomial




```

1 \begin{psgraph}[arrows=->,Dx=1,Dy=100,xsubticks=1,ysubticks=1](0,0)(0,-600)
  (10,600){4.5in}{4.5in}
2 \listplot[plotstyle=dots]{\Poly}
3 %note that the valuewidth needs to be large for debugging matrices
4 \listplot[valuewidth=20,PstDebug=1,decimals=2,EqPos=0.5 -200,plotstyle=GLLSR,
  MaPos=7 500,MaScale=0.5,PolyOrder=4,plotpoints=400,Yint=500]{\Poly}
5 \listplot[linestyle=dashed,decimals=2,EqPos=0.5 -400,plotstyle=GLLSR,PolyOrder
  =4,plotpoints=400]{\Poly}
6 %\listplot[decimals=2,EqPos=0.5 -200,plotstyle=GLLSR,PolyOrder=10,plotpoints
  =400]{\Power}
7 \end{psgraph}

```

9 LinetoXAxis respects scalepoints.




```

1 \begin{psgraph}[arrows=<->,Dx=1,Dy=1,xsubticks=1,ysubticks=1](0,0)(0,0)(10,10)
   {4in}{4in}
2 \pstScalePoints(0.5,0.25){2 add}{16 add}
3 \listplot[plotstyle=line]{\Linear}
4 \listplot[arrows=<- ,plotstyle=LineToXAxis]{\Linear}
5 \pstScalePoints(1,1){}{}
6 \rput[lb](1,2){Scaled fluid velocity distribution on a plot of the physical
   system.}
7 \end{psgraph}

```

10 Prepare Points Modification




```

1 \begin{psgraph}[arrows=->,Dx=1,Dy=1,xsubticks=1,ysubticks=1](0,0)(0,0)(15,30)
   {4.5in}{4.5in}
2 \listplot[plotstyle=line,plotNoMax=2,plotNo=1]{\LinearA}
3 \listplot[plotstyle=line,plotNoMax=2,plotNo=2]{\LinearA}
4 \listplot[plotstyle=line,linestyle=dashed,plotNoMax=2,plotNo=1,plotNoTwo=2,
   plotNoTwoFunc=add 2 div]{\LinearA}
5 \rput[lb](10,18){1st Column}
6 \rput[lb](10,29){2nd Column}
7 \rput[lb](10,24){Average of 1st and 2nd Columns}
8 \end{psgraph}

```

11 PrintCoor Demo



```

1 \begin{psgraph}[arrows=->,Dx=1,Dy=1,xsubticks=1,ysubticks=1](0,0)(10,15)
   {4.5in}{4.5in}
2 %PrintCoor Demo
3 \psset{xEnd=,xStart=,decimals=2,valuewidth=50,fontscale=10,PstDebug=1}
4 \pstScalePoints(1,1){0.75 mul}{0.5 exp 3 mul}
5 \listplot[plotstyle=PrintCoor,plotNoMax=1,plotNo=1,PstDebug=0,relxerr=0,
   relyerr=0.1]{\Linear}
6 \listplot[plotstyle=dots,plotNoMax=1,plotNo=1]{\Linear}
7 \pstScalePoints(1,1){}{}
8 \end{psgraph}

```

12 List of all optional arguments for pst-fit

Key	Type	Default
ScyBase	boolean	true
ScxBasis	boolean	true
plotNoTwo	ordinary	[none]
plotNoTwoFunc	ordinary	[none]
relxerr	ordinary	[none]
relyerr	ordinary	[none]
yShift	ordinary	[none]
science	boolean	true
EqPos	ordinary	
MaPos	ordinary	
MaScale	ordinary	
ShowEq	boolean	true
PolyOrder	ordinary	
ReduceOrder	boolean	true
PowerFit	boolean	true
LogEFit	boolean	true
LogTFit	boolean	true
ExpFit	boolean	true
GaussFit	boolean	true
RecipFit	boolean	true
CustomFit	boolean	true
FXtrans	ordinary	
FYtrans	ordinary	
RYtrans	ordinary	
Yint	ordinary	
CheckZeroX	ordinary	
CheckZeroY	ordinary	

References

- [1] Hendri Adriaens. xkeyval package. [CTAN:/macros/latex/contrib/xkeyval](https://ctan.org/ctan-archive/macros/latex/contrib/xkeyval), 2004.
- [2] Denis Girou. Présentation de PSTricks. *Cahier GUTenberg*, 16:21–70, April 1994.
- [3] Michel Goossens, Frank Mittelbach, Sebastian Rahtz, Denis Roegel, and Herbert Voß. *The L^AT_EX Graphics Companion*. Addison-Wesley Publishing Company, Reading, Mass., 2007.
- [4] Alan Hoenig. *T_EX Unbound: L^AT_EX & T_EX Strategies, Fonts, Graphics, and More*. Oxford University Press, London, 1998.
- [5] Laura E. Jackson and Herbert Voß. Die plot-funktionen von pst-plot. *Die T_EXnische Komödie*, 2/02:27–34, June 2002.
- [6] Nikolai G. Kollock. *PostScript richtig eingesetzt: vom Konzept zum praktischen Einsatz*. IWT, Vaterstetten, 1989.
- [7] Frank Mittelbach and Michel Goossens et al. *The L^AT_EX Companion*. Addison-Wesley Publishing Company, Boston, second edition, 2004.
- [8] Herbert Voß. Die mathematischen Funktionen von PostScript. *Die T_EXnische Komödie*, 1/02, March 2002.
- [9] Herbert Voß. *PSTricks Grafik für T_EX und L^AT_EX*. DANTE – Lehmanns, Heidelberg/Berlin, 6. edition, 2010.
- [10] Herbert Voß. *PSTricks Graphics for L^AT_EX*. UIT, Cambridge, 1 edition, 2011.
- [11] Timothy Van Zandt. *PSTricks - PostScript macros for generic T_EX*. <http://www.tug.org/application/PSTricks>, 1993.
- [12] Timothy Van Zandt. *multido.tex - a loop macro, that supports fixed-point addition*. [CTAN:/graphics/pstricks/generic/multido.tex](https://ctan.org/ctan-archive/graphics/pstricks/generic/multido.tex), 1997.
- [13] Timothy Van Zandt. *pst-plot: Plotting two dimensional functions and data*. [CTAN:/graphics/pstricks/generic/pst-plot.tex](https://ctan.org/ctan-archive/graphics/pstricks/generic/pst-plot.tex), 1999.
- [14] Timothy Van Zandt and Denis Girou. Inside PSTricks. *TUGboat*, 15:239–246, September 1994.