

The soulutf8 package

Heiko Oberdiek
<heiko.oberdiek at gmail.com>

2007/09/09 v1.0

Abstract

This package extends package `soul` and adds some support for UTF-8. Namely the input encodings `utf8.def` from package `inputenc` and package `ucs`'s `utf8x.def` are supported.

Contents

1	Documentation	2
1.1	Patch	2
1.2	Future	2
2	Implementation	2
2.1	Reload check and package identification	2
2.2	Catcodes	3
2.3	Loading packages	4
2.3.1	plain \TeX	5
2.3.2	\LaTeX	5
2.3.3	$\epsilon\text{-}\text{\TeX}$	5
2.4	Macro for redefinitions	6
2.5	Redefinition of <code>\SOUL@eval</code>	6
2.6	UTF-8 analysis	9
2.6.1	Help strings	9
2.6.2	Support for <code>utf8.def</code>	10
2.6.3	Support for <code>utf8x.def</code>	10
2.7	Actions for UTF-8 sequences	11
2.7.1	Redefinition of <code>\SOUL@splittoken</code>	11
2.8	Patches	12
3	Test	15
3.1	Catcode checks for loading	15
3.2	\LaTeX tests	16
3.2.1	Driver definitions	17
3.2.2	Test macros	19
3.2.3	Testing	22
4	Installation	22
4.1	Download	22
4.2	Bundle installation	23
4.3	Package installation	23
4.4	Refresh file name databases	23
4.5	Some details for the interested	23
5	Catalogue	24
6	References	25

7 History	25
[2007/09/09 v1.0]	25
8 Index	25

1 Documentation

This package `soulutf8` does not have own options and does not define new user commands. Any option is passed to package `soul` [1] that is loaded first. Then some internal macros of `soul` are redefined to add support for UTF-8. The following input encodings are supported:

```
utf8      LATEX base    TDS:tex/latex/base/utf8.def [3]
utf8x     Package ucs   TDS:tex/latex/ucs/utf8x.def [2]
```

UTF-8 byte sequences are added as token group to a word, even if these UTF-8 characters are some kind of hyphen or space. As exception the following three Unicode characters are handled specially:

Slot	Name	Action
U+00A0	NO-BREAK SPACE	like ~
U+2013	EN DASH	--
U+2014	EM DASH	---

1.1 Patch

Also package `soulutf8` tries to patch package `soul` to improve its behaviour:

- A problem with additional levels of curly braces is fixed. As advantage more implicate kernings are detected. However, the result may be incompatible with the original behaviour of package `soul` because of these respected implicate kernings.
- ε -T_EX, especially `\unexpanded` is supported. This allows a better protection of token groups (`\mbox{...}`, `math`, ...).

1.2 Future

Currently package `soul` does not seem to be maintained. Nevertheless if there will be a new version that adds support for UTF-8, then this package may become obsolete.

2 Implementation

```
1 < *package >
```

2.1 Reload check and package identification

Reload check, especially if the package is not used with L^AT_EX.

```
2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3 \catcode13=5 % ^M
4 \endlinechar=13 %
5 \catcode35=6 % #
6 \catcode39=12 % '
7 \catcode44=12 % ,
8 \catcode45=12 % -
9 \catcode46=12 % .
10 \catcode58=12 % :
11 \catcode64=11 % @
```

```

12 \catcode123=1 % {
13 \catcode125=2 % }
14 \expandafter\let\expandafter\x\csname ver@soulutf8.sty\endcsname
15 \ifx\x\relax % plain-TeX, first loading
16 \else
17   \def\empty{}%
18   \ifx\x\empty % LaTeX, first loading,
19     % variable is initialized, but \ProvidesPackage not yet seen
20   \else
21     \expandafter\ifx\csname PackageInfo\endcsname\relax
22       \def\x#1#2{%
23         \immediate\write-1{Package #1 Info: #2.}%
24       }%
25     \else
26       \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27     \fi
28     \x{soulutf8}{The package is already loaded}%
29     \aftergroup\endinput
30   \fi
31 \fi
32 \endgroup%

```

Package identification:

```

33 \begingroup\catcode61\catcode48\catcode32=10\relax%
34 \catcode13=5 % ^M
35 \endlinechar=13 %
36 \catcode35=6 % #
37 \catcode39=12 % '
38 \catcode40=12 % (
39 \catcode41=12 % )
40 \catcode44=12 % ,
41 \catcode45=12 % -
42 \catcode46=12 % .
43 \catcode47=12 % /
44 \catcode58=12 % :
45 \catcode64=11 % @
46 \catcode91=12 % [
47 \catcode93=12 % ]
48 \catcode123=1 % {
49 \catcode125=2 % }
50 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
51   \def\x#1#2#3[#4]{\endgroup
52     \immediate\write-1{Package: #3 #4}%
53     \xdef#1{#4}%
54   }%
55 \else
56   \def\x#1#2[#3]{\endgroup
57     #2[#{#3}]%
58     \ifx#1\@undefined
59       \xdef#1{#3}%
60     \fi
61     \ifx#1\relax
62       \xdef#1{#3}%
63     \fi
64   }%
65 \fi
66 \expandafter\x\csname ver@soulutf8.sty\endcsname
67 \ProvidesPackage{soulutf8}%
68 [2007/09/09 v1.0 Permit use of UTF-8 characters in soul (H0)]%

```

2.2 Catcodes

```

69 \begingroup\catcode61\catcode48\catcode32=10\relax%

```

```

70 \catcode13=5 % ^^M
71 \endlinechar=13 %
72 \catcode123=1 % {
73 \catcode125=2 % }
74 \catcode64=11 % @
75 \def\x{\endgroup
76   \expandafter\edef\csname SOuL@AtEnd\endcsname{%
77     \endlinechar=\the\endlinechar\relax
78     \catcode13=\the\catcode13\relax
79     \catcode32=\the\catcode32\relax
80     \catcode35=\the\catcode35\relax
81     \catcode61=\the\catcode61\relax
82     \catcode64=\the\catcode64\relax
83     \catcode123=\the\catcode123\relax
84     \catcode125=\the\catcode125\relax
85   }%
86 }%
87 \x\catcode61\catcode48\catcode32=10\relax%
88 \catcode13=5 % ^^M
89 \endlinechar=13 %
90 \catcode35=6 % #
91 \catcode64=11 % @
92 \catcode123=1 % {
93 \catcode125=2 % }
94 \def\TMP@EnsureCode#1#2{%
95   \edef\SOuL@AtEnd{%
96     \SOuL@AtEnd
97     \catcode#1=\the\catcode#1\relax
98   }%
99   \catcode#1=#2\relax
100 }
101 \TMP@EnsureCode{10}{12}% ^^J
102 \TMP@EnsureCode{33}{12}% !
103 \TMP@EnsureCode{34}{12}% "
104 \TMP@EnsureCode{36}{3}% $
105 \TMP@EnsureCode{39}{12}% '
106 \TMP@EnsureCode{40}{12}% (
107 \TMP@EnsureCode{41}{12}% )
108 \TMP@EnsureCode{42}{12}% *
109 \TMP@EnsureCode{43}{12}% +
110 \TMP@EnsureCode{44}{12}% ,
111 \TMP@EnsureCode{45}{12}% -
112 \TMP@EnsureCode{46}{12}% .
113 \TMP@EnsureCode{47}{12}% /
114 \TMP@EnsureCode{58}{12}% :
115 \TMP@EnsureCode{60}{12}% <
116 \TMP@EnsureCode{62}{12}% >
117 \TMP@EnsureCode{91}{12}% [
118 \TMP@EnsureCode{93}{12}% ]
119 \TMP@EnsureCode{94}{7}% ^
120 \TMP@EnsureCode{96}{12}% `
121 \TMP@EnsureCode{126}\active % ~
122 \TMP@EnsureCode{128}{12}% ^^80
123 \TMP@EnsureCode{147}{12}% ^^93
124 \TMP@EnsureCode{148}{12}% ^^94
125 \TMP@EnsureCode{160}{12}% ^^a0
126 \TMP@EnsureCode{194}{12}% ^^c2
127 \TMP@EnsureCode{226}{12}% ^^e2
128 \edef\SOuL@AtEnd{\SOuL@AtEnd\noexpand\endinput}

```

2.3 Loading packages

Package soul uses `\documentclass` to detect L^AT_EX.

129 \ifx\documentclass\@undefined

2.3.1 plain T_EX

First we check, whether package soul is already loaded.

130 \expandafter\ifx\csname SOUL@\endcsname\relax

In case of plain T_EX package soul defines some macros in a simple manner that will break the definitions of miniltx.tex, for example. Therefore these macros are first saved and restored afterwards.

```

131 \let\Soul@orgDeclareRobustCommand\DeclareRobustCommand
132 \let\Soul@orgnewcommand \newcommand
133 \let\Soul@orgDeclareOption \DeclareOption
134 \let\Soul@orgPackageError \PackageError
135 \def\Soul@restorelatexcmds{%
136 \let\DeclareRobustCommand\Soul@orgDeclareRobustCommand
137 \let\newcommand \Soul@orgnewcommand
138 \let\DeclareOption \Soul@orgDeclareOption
139 \let\PackageError \Soul@orgPackageError
140 }%
141 \input soul.sty\relax
142 \Soul@restorelatexcmds
143 \fi

```

\SOUL@error Package soul's use of \PackageError is replaced by \@PackageError of package infwarerr.

```

144 \input infwarerr.sty\relax
145 \let\Soul@orgSOUL@error\SOUL@error
146 \def\SOUL@error{%
147 \begingroup
148 \let\PackageError\@PackageError
149 \Soul@orgSOUL@error
150 \endgroup
151 }%

```

152 \input etexcmds.sty\relax

\@onelevel@sanitize Define L^AT_EX's \@onelevel@sanitize if not already available.

```

153 \expandafter\ifx\csname @onelevel@sanitize\endcsname\relax
154 \def\@onelevel@sanitize#1{%
155 \edef#1{%
156 \expandafter\strip@prefix\meaning#1%
157 }%
158 }%

```

\strip@prefix

```

159 \def\strip@prefix#1>{%}%
160 \fi
161 \else

```

2.3.2 L^AT_EX

```

162 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{soul}}%
163 \ProcessOptions\relax
164 \RequirePackage{soul}[2003/11/17]%
165 \RequirePackage{infwarerr}[2007/09/09]%
166 \RequirePackage{etexcmds}[2007/09/09]%
167 \fi

```

2.3.3 -T_EX

In plain T_EX command \+ is an *outer* macro. Therefore numbers are used to avoid problems.

```

168 \ifetex@unexpanded
169 \catcode33=14 % '!': comment
170 \catcode43=9 % '+': ignore
171 \else
172 \catcode33=9 % '!': ignore
173 \catcode43=14 % '+': comment
174 \fi

```

2.4 Macro for redefinitions

`\SOuL@redefine`

```

175 \def\SOuL@redefine#1{%
176 \begingroup
177 \def\SOuL@cmd{#1}%
178 \afterassignment\SOuL@cmdcheck
179 \def\SOuL@temp
180 }

```

`\SOuL@cmdcheck`

```

181 \def\SOuL@cmdcheck{%
182 \expandafter\ifx\SOuL@cmd\SOuL@temp
183 \else
184 \edef\SOuL@temp*{\expandafter\string\SOuL@cmd}%
185 \@PackageWarningNoLine{soulutf8}{%
186 Command \SOuL@temp* has changed.\MessageBreak
187 Supported versions of package `soul': 2003/11/17.\MessageBreak
188 Depending on the unknown changes the redefinition\MessageBreak
189 of \SOuL@temp* may not behave correctly%
190 }%
191 \fi
192 \expandafter\endgroup
193 \expandafter\def\SOuL@cmd
194 }

```

2.5 Redefinition of `\SOUL@eval`

`\SOUL@eval` Macro `\SOUL@eval` is redefined to add detection of the first byte of a UTF-8 sequence. Because `\SOUL@eval` is overwritten, a warning is issued, if the contents of `\SOUL@eval` is not as expected.

```

195 \SOuL@redefine\SOUL@eval{%

```

First the expected definition.

```

196 \def\SOUL@n*##1{\SOUL@scan}%
197 \if\noexpand\SOUL@@\SOUL@spc
198 \else
199 \SOUL@ignorespacesfalse
200 \fi
201 \ifnum\SOUL@minus=\thr@@
202 \SOUL@flushminus
203 \else\ifnum\SOUL@comma=\tw@
204 \SOUL@flushcomma
205 \else\ifnum\SOUL@apo=\tw@
206 \SOUL@flushapo
207 \else\ifnum\SOUL@grave=\tw@
208 \SOUL@flushgrave
209 \fi\fi\fi\fi
210 \ifx\SOUL@@-\else\SOUL@flushminus\fi
211 \ifx\SOUL@,@\else\SOUL@flushcomma\fi
212 \ifx\SOUL@@'\else\SOUL@flushapo\fi
213 \ifx\SOUL@@`\else\SOUL@flushgrave\fi
214 \ifx\SOUL@@-%
215 \advance\SOUL@minus\@ne

```

[illegible]

```

278 \fi\fi\fi\fi
279 \SOUL@n*%
280 }{%
```

Now the redefined version follows.

```

281 \def\SOUL@n*##1{\SOUL@scan}%
282 \if\noexpand\SOUL@@\SOUL@spc
283 \else
284 \SOUL@ignorespacesfalse
285 \fi
286 \ifnum\SOUL@minus=\thr@@
287 \SOUL@flushminus
288 \else\ifnum\SOUL@comma=\tw@
289 \SOUL@flushcomma
290 \else\ifnum\SOUL@apo=\tw@
291 \SOUL@flushapo
292 \else\ifnum\SOUL@grave=\tw@
293 \SOUL@flushgrave
294 \fi\fi\fi\fi
295 \ifx\SOUL@@-\else\SOUL@flushminus\fi
296 \ifx\SOUL@,@\else\SOUL@flushcomma\fi
297 \ifx\SOUL@@'\else\SOUL@flushapo\fi
298 \ifx\SOUL@@`\else\SOUL@flushgrave\fi
299 \ifx\SOUL@@-%
300 \advance\SOUL@minus\@ne
301 \else\ifx\SOUL@@,%
302 \advance\SOUL@comma\@ne
303 \else\ifx\SOUL@@'%
304 \advance\SOUL@apo\@ne
305 \else\ifx\SOUL@@`%
306 \advance\SOUL@grave\@ne
307 \else
308 \SOUL@flushminus
309 \SOUL@flushcomma
310 \SOUL@flushapo
311 \SOUL@flushgrave
312 \ifx\SOUL@@\SOUL@stop
313 \def\SOUL@n*{%
314 \SOUL@doword
315 \SOUL@eventuallyexhyphen\null
316 }%
317 \else\ifx\SOUL@@\par
318 \def\SOUL@n*\par{\par\leavevmode\SOUL@scan}%
319 \else\if\noexpand\SOUL@@\SOUL@spc
320 \SOUL@doword
321 \SOUL@eventuallyexhyphen\null
322 \ifSOUL@ignorespaces
323 \else
324 \SOUL@everySPACE{}%
325 \fi
326 \def\SOUL@n* {\SOUL@scan}%
327 \else\ifx\SOUL@@\%
328 \SOUL@doword
329 \SOUL@eventuallyexhyphen\null
330 \SOUL@everySPACE{\unskip\nobreak\hfil\break}%
331 \SOUL@ignorespacestrue
332 \else\ifx\SOUL@@~%
333 \SOUL@doword
334 \SOUL@eventuallyexhyphen\null
335 \SOUL@everySPACE{\nobreak}%
336 \else\ifx\SOUL@@\slash
337 \SOUL@doword
338 \SOUL@eventuallyexhyphen{/}%
```



```

339      \SOUL@exhyphen{}/}%
340    \else\ifx\SOUL@@\mbox
341      \def\SOUL@n*{\SOUL@addprotect}%
342    \else\ifx\SOUL@@\hbox
343      \def\SOUL@n*{\SOUL@addprotect}%
344    \else\ifx\SOUL@@\soulomit
345      \def\SOUL@n*\soulomit##1{%
346        \SOUL@doword
347        {\spaceskip\SOUL@spaceskip##1}%
348        \SOUL@scan
349      }%
350    \else\ifx\SOUL@@\break
351      \SOUL@doword
352      \break
353    \else\ifx\SOUL@@\linebreak
354      \SOUL@doword
355      \SOUL@everyspace{\linebreak}%
356    \else\ifcat\bgroup\noexpand\SOUL@@
357      \def\SOUL@n*{\SOUL@addgroup{}}}%
358    \else\ifcat$\noexpand\SOUL@@
359      \def\SOUL@n*{\SOUL@addmath}%
360    \else

```

[illegible]

2.6.1 Help strings

```

395 \edef\Soul@chartwo{\string 2}
396 \edef\Soul@charthree{\string 3}
397 \def\Soul@empty{}

```

2.6.2 Support for utf8.def

\Soul@analyzeutfviii

```

398 \begingroup
399 \edef\x{\endgroup
400   \def\noexpand\Soul@analyzeutfviii{%
401     \noexpand\expandafter\noexpand\Soul@checkutfviii
402     \noexpand\meaning\noexpand\Soul@@
403     \Soul@stringUTFviii\Soul@stringoctets
404     \noexpand\@nil
405   }%
406   \def\noexpand\Soul@checkutfviii
407     #1\Soul@stringUTFviii##2\Soul@stringoctets##3\noexpand\@nil
408   }%
409 \x{%
410   \def\Soul@temp{#2}%
411   \chardef\Soul@octets=%
412     \ifx\Soul@temp\Soul@stringtwo
413       \tw@
414     \else\ifx\Soul@temp\Soul@stringthree
415       \thr@@
416     \else\ifx\Soul@temp\Soul@stringfour
417       4 %
418     \else
419       \z@
420     \fi\fi\fi
421 }

```

2.6.3 Support for utf8x.def

\Soul@analyzeutfviiix

```

422 \begingroup
423 \edef\x{\endgroup
424   \def\noexpand\Soul@analyzeutfviiix{%
425     \noexpand\expandafter\noexpand\Soul@checkutfviiix
426     \noexpand\meaning\noexpand\Soul@@
427     \Soul@stringmacrocolon\Soul@charhash1{}{}{}{}%
428     \Soul@stringcsnameu\Soul@stringundeferr
429     \noexpand\@nil
430   }%

```

\Soul@checkutfviiix

```

431   \def\noexpand\Soul@checkutfviiix
432     ##1\Soul@stringmacrocolon\Soul@charhash1##2##3##4##5##6%
433     \Soul@stringcsnameu##7\Soul@stringundeferr##8\noexpand\@nil
434   }%
435 \x{%
436   \def\Soul@temp{#7}%
437   \ifx\Soul@temp\Soul@empty
438     \chardef\Soul@octets=\z@
439   \else
440     \def\Soul@temp{#5}%
441     \ifx\Soul@temp\Soul@charthree
442       \chardef\Soul@octets=4 %
443     \else
444       \def\Soul@temp{#3}%
445       \ifx\Soul@temp\Soul@chartwo
446         \chardef\Soul@octets=\thr@@
447       \else

```

```

448      \chardef\Soul@octets=\tw@
449      \fi
450      \fi
451      \fi
452 }

```

2.7 Actions for UTF-8 sequences

`\Soul@addtwooctets`

```

453 \def\Soul@addtwooctets#1#2{%
454   \def\Soul@temp{#1#2}%
455   \@onelevel@sanitize\Soul@temp
456   \ifx\Soul@temp\Soul@stringnobreakspace
457     \SOUL@doword
458     \SOUL@eventuallyexhyphen\null
459     \SOUL@everySPACE{\nobreak}%
460     \let\Soul@next\Soul@scan
461   \else
462     \def\Soul@next{%
463       ! \SOUL@addtoken{\noexpand#1\noexpand#2}}%
464     + \SOUL@addtoken{\etex@unexpanded{#1#2}}}%
465     }%
466   \fi
467   \Soul@next
468 }

```

`\Soul@addthreeoctets`

```

469 \def\Soul@addthreeoctets#1#2#3{%
470   \def\Soul@temp{#1#2#3}%
471   \@onelevel@sanitize\Soul@temp
472   \ifx\Soul@temp\Soul@stringendash
473     \SOUL@doword
474     \SOUL@eventuallyexhyphen{-}%
475     \SOUL@exhyphen{--}%
476     \let\Soul@next\Soul@scan
477   \else
478     \ifx\Soul@temp\Soul@stringemdash
479       \SOUL@doword
480       \SOUL@eventuallyexhyphen{-}%
481       \SOUL@exhyphen{---}%
482       \let\Soul@next\Soul@scan
483     \else
484       \def\Soul@next{%
485         ! \SOUL@addtoken{\noexpand#1\noexpand#2\noexpand#3}}%
486       + \SOUL@addtoken{\etex@unexpanded{#1#2#3}}}%
487       }%
488     \fi
489   \fi
490   \Soul@next
491 }

```

`\Soul@addfouroctets`

```

492 \def\Soul@addfouroctets#1#2#3#4{%
493   ! \SOUL@addtoken{\noexpand#1\noexpand#2\noexpand#3\noexpand#4}}%
494   + \SOUL@addtoken{\etex@unexpanded{#1#2#3#4}}}%
495 }

```

2.7.1 Redefinition of `\SOUL@splittoken`

`\SOUL@splittoken` Macro `\SOUL@splittoken` separates the first token or token group from a word and redefines the word to contain the remaining tokens. However if the remaining tokens are a token group, then the curly braces will be removed and the token

group is splitted by the next call of `\SOUL@splittoken`. The redefinition avoids the removal of curly braces around the remaining tokens.

```

496 \SOUL@redefine\SOUL@splittoken#1#2\SOUL@stop{%
497   \global\SOUL@token={#1}%
498   \global\SOUL@word={#2}%
499 }#1{%
500   \global\SOUL@token={#1}%
501   \SOUL@remainingtoken\relax
502 }

```

`\SOUL@remainingtoken`

```

503 \def\SOUL@remainingtoken#1\SOUL@stop{%
504   \global\SOUL@word=\expandafter{\@gobble#1}%
505 }

```

2.8 Patches

The fixed `\SOUL@splittoken` allows to remove the double sets of curly braces in other macros of package `soul`. The benefit is that implicate kernings are more often detected and fixes a bug in package `soul`. The disadvantage is incompatibility. The width of the resulting strings may change.

`\SOUL@flushcomma`

```

506 \SOUL@redefine\SOUL@flushcomma{%
507   \ifcase\SOUL@comma
508   \or
509     \edef\x{\SOUL@word={\the\SOUL@word,}}\x
510   \or
511     \edef\x{\SOUL@word={\the\SOUL@word{, ,}}}\x
512   \fi
513   \SOUL@comma\z@
514 }{%
515   \ifcase\SOUL@comma
516   \or
517     \edef\x{\SOUL@word={\the\SOUL@word,}}\x
518   \or
519     \edef\x{\SOUL@word={\the\SOUL@word{, ,}}}\x
520   \fi
521   \SOUL@comma\z@
522 }

```

`\SOUL@flushapo`

```

523 \SOUL@redefine\SOUL@flushapo{%
524   \ifcase\SOUL@apo
525   \or
526     \edef\x{\SOUL@word={\the\SOUL@word'}}\x
527   \or
528     \edef\x{\SOUL@word={\the\SOUL@word{' '}}}\x
529   \fi
530   \SOUL@apo\z@
531 }{%
532   \ifcase\SOUL@apo
533   \or
534     \edef\x{\SOUL@word={\the\SOUL@word'}}\x
535   \or
536     \edef\x{\SOUL@word={\the\SOUL@word{' '}}}\x
537   \fi
538   \SOUL@apo\z@
539 }

```

`\SOUL@flushgrave`

```

540 \SOuL@redefine\SOUL@flushgrave{%
541   \ifcase\SOUL@grave
542   \or
543     \edef\x{\SOUL@word={\the\SOUL@word`}}\x
544   \or
545     \edef\x{\SOUL@word={\the\SOUL@word{``}}}\x
546   \fi
547   \SOUL@grave\z@
548 }{%
549   \ifcase\SOUL@grave
550   \or
551     \edef\x{\SOUL@word={\the\SOUL@word`}}\x
552   \or
553     \edef\x{\SOUL@word={\the\SOUL@word{``}}}\x
554   \fi
555   \SOUL@grave\z@
556 }

```

\SOUL@addgroup

```

557 \SOuL@redefine\SOUL@addgroup#1#2{%
558   {%
559     \let\protect\noexpand
560     \edef\x{%
561       \global\SOUL@word={%
562         \the\SOUL@word
563         {\noexpand#1#2}}%
564     }%
565   }%
566   \x
567 }%
568 \SOUL@scan
569 }#1#2{%
570   \begingroup
571   \let\protect\noexpand
572   \edef\x{\endgroup
573     \SOUL@word={%
574       \the\SOUL@word
575       {\noexpand#1{#2}}%
576       {\etex@unexpanded{#1{#2}}}%
577     }%
578   }%
579   \x
580   \SOUL@scan
581 }

```

\SOUL@addmath

```

582 \SOuL@redefine\SOUL@addmath$#1${%
583   {%
584     \let\protect\noexpand
585     \edef\x{%
586       \global\SOUL@word={%
587         \the\SOUL@word
588         {\hbox{ $#1$ }}%
589       }%
590     }%
591     \x
592   }%
593   \SOUL@scan
594 }$#1${%
595   \begingroup
596   \let\protect\noexpand
597   \edef\x{\endgroup
598     \SOUL@word={%

```

```

599      \the\SOUL@word
600 !      {\hbox{ $#1$}}}%
601 +      {\etex@unexpanded{\hbox{ $#1$}}}%
602    }%
603  }%
604  \x
605  \SOUL@scan
606 }

```

\SOUL@addprotect

```

607 \SOuL@redefine\SOUL@addprotect#1#2{%
608   {%
609     \let\protect\noexpand
610     \edef\x{%
611       \global\SOUL@word={%
612         \the\SOUL@word
613         {\hbox{#2}}}%
614     }%
615   }%
616   \x
617 }%
618 \SOUL@scan
619 }#1#2{%
620   \begingroup
621     \let\protect\noexpand
622     \edef\x{\endgroup
623       \SOUL@word={%
624         \the\SOUL@word
625         {\hbox{#2}}}%
626     +   {\etex@unexpanded{\hbox{#2}}}%
627   }%
628 }%
629 \x
630 \SOUL@scan
631 }

```

\SOUL@addtoken

```

632 + \SOuL@redefine\SOUL@addtoken#1{%
633 +   \edef\x{%
634 +     \SOUL@word={%
635 +       \the\SOUL@word
636 +       \noexpand#1%
637 +     }%
638 +   }%
639 +   \x
640 +   \SOUL@scan
641 + }#1{%
642 +   \edef\x{%
643 +     \SOUL@word={%
644 +       \the\SOUL@word
645 +       \etex@unexpanded{#1}%
646 +     }%
647 +   }%
648 +   \x
649 +   \SOUL@scan
650 + }%

```

```

651 \SOuL@AtEnd%

```

```

652 </package>

```

3 Test

3.1 Catcode checks for loading

```
653 <*test1>
654 \catcode`\{=1 %
655 \catcode`\}=2 %
656 \catcode`\#=6 %
657 \catcode`\@=11 %
658 \expandafter\ifx\csname count@\endcsname\relax
659 \countdef\count@=255 %
660 \fi
661 \expandafter\ifx\csname @gobble\endcsname\relax
662 \long\def\@gobble#1{}%
663 \fi
664 \expandafter\ifx\csname @firstofone\endcsname\relax
665 \long\def\@firstofone#1{#1}%
666 \fi
667 \expandafter\ifx\csname loop\endcsname\relax
668 \expandafter\@firstofone
669 \else
670 \expandafter\@gobble
671 \fi
672 {%
673 \def\loop#1\repeat{%
674 \def\body{#1}%
675 \iterate
676 }%
677 \def\iterate{%
678 \body
679 \let\next\iterate
680 \else
681 \let\next\relax
682 \fi
683 \next
684 }%
685 \let\repeat=\fi
686 }%
687 \def\RestoreCatcodes{}
688 \count@=0 %
689 \loop
690 \edef\RestoreCatcodes{%
691 \RestoreCatcodes
692 \catcode\the\count@=\the\catcode\count@\relax
693 }%
694 \ifnum\count@<255 %
695 \advance\count@ 1 %
696 \repeat
697
698 \def\RangeCatcodeInvalid#1#2{%
699 \count@=#1\relax
700 \loop
701 \catcode\count@=15 %
702 \ifnum\count@<#2\relax
703 \advance\count@ 1 %
704 \repeat
705 }
706 \def\RangeCatcodeCheck#1#2#3{%
707 \count@=#1\relax
708 \loop
709 \ifnum#3=\catcode\count@
710 \else
```

```

711     \errmessage{%
712         Character \the\count@\space
713         with wrong catcode \the\catcode\count@\space
714         instead of \number#3%
715     }%
716     \fi
717     \ifnum\count@<#2\relax
718         \advance\count@ 1 %
719     \repeat
720 }
721 \def\space{ }
722 \expandafter\ifx\csname LoadCommand\endcsname\relax
723     \def\LoadCommand{\input soulutf8.sty\relax}%
724 \fi
725 \def\Test{%
726     \RangeCatcodeInvalid{0}{47}%
727     \RangeCatcodeInvalid{58}{64}%
728     \RangeCatcodeInvalid{91}{96}%
729     \RangeCatcodeInvalid{123}{255}%
730     \catcode`\@=12 %
731     \catcode`\|=0 %
732     \catcode`\%=14 %
733     \LoadCommand
734     \RangeCatcodeCheck{0}{36}{15}%
735     \RangeCatcodeCheck{37}{37}{14}%
736     \RangeCatcodeCheck{38}{47}{15}%
737     \RangeCatcodeCheck{48}{57}{12}%
738     \RangeCatcodeCheck{58}{63}{15}%
739     \RangeCatcodeCheck{64}{64}{12}%
740     \RangeCatcodeCheck{65}{90}{11}%
741     \RangeCatcodeCheck{91}{91}{15}%
742     \RangeCatcodeCheck{92}{92}{0}%
743     \RangeCatcodeCheck{93}{96}{15}%
744     \RangeCatcodeCheck{97}{122}{11}%
745     \RangeCatcodeCheck{123}{255}{15}%
746     \RestoreCatcodes
747 }
748 \Test
749 \csname @@end\endcsname
750 \end
751 </test1>

```

3.2 L^AT_EX tests

```

752 <*test2 j test3 j test4 j test5>
753 <noetex> \let\SavedUnexpanded\unexpanded
754 <noetex> \let\unexpanded\UNDEFINED
755 \NeedsTeXFormat{LaTeX2e}
756 \documentclass{article}
757 \usepackage[Ti]{fontenc}
758 \usepackage{lmodern}
759 \usepackage{textcomp}
760 \usepackage[ngerman]{babel}
761 \expandafter\def\csname ver@hypdestopt.sty\endcsname{}
762 \usepackage[unicode]{hyperref}
763 \usepackage{bookmark}
764 \usepackage{color}
765 \usepackage{soul}[2003/11/17]
766 \makeatletter
767 \newcommand*{\@ifDefined}[1]{%
768     \@ifundefined{#1}{%
769         \@latex@error{%
770             \expandafter\noexpand\csname#1\endcsname undefined%

```



```

771   }\@ehc
772 }%
773 }
774 \newcommand*{\SaveOrg}[1]{%
775   \@ifdefinable{ORG@SOUL@#1}{%
776     \@ifDefined{SOUL@#1}{%
777       \expandafter\let\csname ORG@SOUL@#1\expandafter\endcsname
778         \csname SOUL@#1\endcsname
779     }%
780 }%
781 }
782 \newcommand*{\RestoreOrg}[1]{%
783   \@ifDefined{ORG@SOUL@#1}{%
784     \@ifDefined{SOUL@#1}{%
785       \expandafter\let\csname SOUL@#1\expandafter\endcsname
786         \csname ORG@SOUL@#1\endcsname
787     }%
788 }%
789 }
790 \makeatother
791 \SaveOrg{eval}
792 \SaveOrg{splittoken}
793 \SaveOrg{flushcomma}
794 \SaveOrg{flushapo}
795 \SaveOrg{grave}
796 \SaveOrg{addgroup}
797 \SaveOrg{addmath}
798 \SaveOrg{addprotect}
799 \SaveOrg{addtoken}
800 \usepackage{soulutf8}[2007/09/09]
801 \noetex\let\unexpanded\SavedUnexpanded

```

Input encoding utf8.

```

802 \utf8
803 \usepackage[utf8]{inputenc}
804 \DeclareUnicodeCharacter{00A0}{\nobreakspace}
805 \utf8

```

Input encoding utf8x. Package ucs has a nasty bug, that it redefines \show.

```

806 \utf8x
807 \let\origshow\show
808 \usepackage[utf8x]{inputenc}
809 \AtBeginDocument{%
810   \let\show\origshow
811 }
812 \utf8x

```

3.2.1 Driver definitions

```

813 \makeatletter

```

\an The definition for \an is taken from the documentation of package soul.

```

814 \DeclareRobustCommand*\an{%
815   \def\SOUL@preamble{$\sim$P}$}%
816   \def\SOUL@everyspace##1{##1\texttt{\char`~}\linebreak[2]}%
817   \def\SOUL@postamble{$\sim$E}$}%
818   \def\SOUL@everyhyphen{$\sim$-}$\linebreak[1]}%
819   \def\SOUL@everyexhyphen##1{##1$\sim$=}$}%
820   \def\SOUL@everysyllable{$\sim$S}$}%
821   \def\SOUL@everytoken{\the\SOUL@token$\sim$T}$}%
822   \def\SOUL@everylowerthan{$\sim$L}$}%
823   \SOUL@
824 }

```

\sy The definition for \sy is taken from the documentation of package soul.

```

825 \DeclareRobustCommand*{\sy}{%
826   \SOUL@setup
827   \def\SOUL@preamble{%
828     \lefthyphenmin=\z@
829     \righthyphenmin=\z@
830   }%
831   \def\SOUL@everyspace##1{##1\space}%
832   \def\SOUL@everysyllable{\the\SOUL@syllable}%
833   \def\SOUL@everyhyphen{%
834     \discretionary{%
835       \SOUL@setkern\SOUL@hyphkern
836       \SOUL@sethyphenchar
837     }{}{%
838       \hbox{\kern1pt$\cdot$}%
839     }%
840   }%
841   \def\SOUL@everyexhyphen##1{%
842     \SOUL@setkern\SOUL@hyphkern
843     \hbox{##1}%
844     \discretionary{}{}{%
845       \SOUL@setkern\SOUL@charkern
846     }%
847   }%
848   \SOUL@
849 }

```

\soulH

```

850 \DeclareRobustCommand*{\soulH}{%
851   \def\SOUL@preamble{%
852     \gdef\SOULH{}%
853     \soulHadd{[]}%
854   }%
855   \def\SOUL@everyspace##1{%
856     \soulHadd{Sp}%
857   }%
858   \def\SOUL@postamble{%
859     \soulHadd{[]}%
860   }%
861   \def\SOUL@everyhyphen{%
862     \soulHadd{Hy}%
863   }%
864   \def\SOUL@everyexhyphen##1{%
865     \soulHadd{Exhy}%
866   }%
867   \def\SOUL@everysyllable{%
868     \soulHadd{Sy}%
869   }%
870   \def\SOUL@everytoken{%
871     \soulHadd{T}%
872   }%
873   \def\SOUL@everylowerthan{%
874     \soulHadd{<}%
875   }%
876   \SOUL@
877 }
878 \newcommand*{\soulHadd}[1]{%
879   #1%
880   \expandafter\gdef\expandafter\soulHstring\expandafter{%
881     \soulHstring
882     #1%
883   }%
884 }

```

3.2.2 Test macros

```

885 \usepackage{qstest}
886 \IncludeTests{*}
887 \LogTests{log}{*}{*}

888 \newsavebox\boxA
889 \newsavebox\boxB
890 \newsavebox\boxC

\TestDriver

891 \newcommand*{\TestDriver}[4]{%
892   \subsection{Driver #1}%
893   \@PackageInfo{soulutf8-test}{* Driver #1}%
894   \expandafter\let\expandafter\testdriver\csname #1\endcsname
895   \def\teststringA{#3}%
896   \def\teststringB{#4}%
897   \begin{qstest}{string-#2-driver-#1}{string,#2,driver,#1}%
898     \@PackageInfo{soulutf8-test}{* Version: soulutf8}%
899     \global\let\soulHstring\@empty
900     \setbox0=\hbox{\expandafter\testdriver\expandafter{\teststringA}}%
901     \let\HstringA\soulHstring
902     \SetTestVBox{\boxA}{\teststringA}%
903     %
904     \@PackageInfo{soulutf8-test}{* Version: soul + patch}%
905     \global\let\soulHstring\@empty
906     \RestoreOrg{eval}%
907     \setbox2=\hbox{\expandafter\testdriver\expandafter{\teststringB}}%
908     \let\HstringB\soulHstring
909     \SetTestVBox{\boxB}{\teststringB}%
910     %
911     \@PackageInfo{soulutf8-test}{* Version: original soul}%
912     \global\let\soulHstring\@empty
913     \RestoreOrg{splittoken}%
914     \RestoreOrg{flushcomma}%
915     \RestoreOrg{flushapo}%
916     \RestoreOrg{grave}%
917     \RestoreOrg{addgroup}%
918     \RestoreOrg{addmath}%
919     \RestoreOrg{addprotect}%
920     \RestoreOrg{addtoken}%
921     \setbox4=\hbox{\expandafter\testdriver\expandafter{\teststringB}}%
922     \let\HstringC\soulHstring
923     \SetTestVBox{\boxC}{\teststringB}%
924     %
925     \TestInfo{0}{soulutf8}%
926     \TestInfo{2}{soul + patch}%
927     \TestInfo{4}{original soul}%
928     \TestInfoVBox
929     \showboxdepth=\maxdimen
930     \showboxbreadth=\maxdimen
931     \tracingonline=\@ne
932     \Expect*{\HstringA}*{\HstringB}%
933     \Expect*{\HstringA}*{\HstringC}%
934     \Expect*{\the\wd0}*{\the\wd2}%
935     \ifdim\wd0=\wd2 %
936     \else
937       \showbox0 %
938       \showbox2 %
939     \fi
940     \Expect*{\the\ht0}*{\the\ht2}%
941     \Expect*{\the\dp0}*{\the\dp2}%
942     \Expect*{\the\wd\boxB}*{\the\wd\boxA}%
943     \Expect*{\the\wd\boxC}*{\the\wd\boxA}%

```

```

944 \Expect*{\the\ht\boxB}*{\the\ht\boxA}%
945 \ifdim\ht\boxB=\ht\boxA
946 \else
947 \showbox\boxA
948 \showbox\boxB
949 \fi
950 \Expect*{\the\ht\boxC}*{\the\ht\boxA}%
951 \Expect*{\the\dp\boxB}*{\the\dp\boxA}%
952 \Expect*{\the\dp\boxC}*{\the\dp\boxA}%
953 \end{qstest}%
954 }

```

\SetTestVBox

```

955 \newcommand*{\SetTestVBox}[2]{%
956 \setbox#1=\vbox{%
957 \hsize=0pt\relax
958 \hfuzz=100mm\relax
959 \expandafter\testdriver\expandafter{#2}%
960 }%
961 }

```

\TestInfo

```

962 \newcommand*{\TestInfo}[2]{%
963 \par
964 \noindent
965 \copy#1\relax
966 \hfill
967 \begin{group}
968 \small
969 \ifdim\wd0=\wd2\relax
970 \ifdim\wd0=\wd4\relax
971 \else
972 \ifnum#1=2 %
973 \raisebox{.5\baselineskip}[0pt][0pt]{%
974 \llap{$\}$ }%
975 \rlap{width = \the\wd#1\relax\space$\}$}%
976 \phantom{width = 999.99999pt}%
977 \quad
978 }%
979 \else
980 \ifnum#1=4 %
981 \rlap{width = \the\wd#1}%
982 \phantom{width = 999.99999pt}%
983 \quad
984 \fi
985 \fi
986 \fi
987 \else
988 \begin{group}
989 \bfseries
990 \rlap{width = \the\wd#1}%
991 \phantom{width = 999.99999pt}%
992 \end{group}
993 \quad
994 \fi
995 \rlap{(#2)}%
996 \phantom{(original soul)}%
997 \end{group}
998 \par
999 }

```

\TestInfoVBox

```

1000 \newcommand*{\TestInfoVBox}{%
1001   \par
1002   \noindent
1003   \mbox{\vrule\relax\space\copy\boxA}%
1004   \ifdim\ht\boxA=\ht\boxB
1005   \else
1006     \hfill
1007     \begin{group}
1008       \small
1009       \rlap{(soulutf8)}%
1010       \phantom{(soulutf8)}%
1011     \end{group}
1012   \par
1013   \noindent
1014   \mbox{\vrule\relax\space\copy\boxB}%
1015   \hfill
1016   \begin{group}
1017     \small
1018     \rlap{(soul)}%
1019     \phantom{(soulutf8)}%
1020   \end{group}
1021 \fi
1022 \par
1023 }

```

\Test

```

1024 \makeatletter
1025 \newcommand*{\Test}[3]{%
1026   \clearpage
1027   \begin{group}
1028     \def\linebreak{\textbackslash linebreak }%
1029     \def\{\{\textbackslash\textbackslash}%
1030     \def\soulomit##1{%
1031       \textbackslash soulomit\textbraceleft##1\textbraceright
1032     }%
1033     \def\mbox##1{%
1034       \textbackslash mbox\textbraceleft##1\textbraceright
1035     }%
1036     \def\abc{\textbackslash abc }%
1037     \def\texttt##1{%
1038       \textbackslash texttt\textbraceleft##1\textbraceright
1039     }%
1040     \def\c##1{%
1041       \textbackslash c\textbraceleft##1\textbraceright
1042     }%
1043     < *utf8x>
1044     \count@=128 %
1045     \loop
1046     \ifnum\count@<256 %
1047       \lccode`\~=\count@
1048       \lowercase{%
1049         \def~{\noexpand~}%
1050       }%
1051       \advance\count@\@ne
1052     \repeat
1053     < /utf8x>
1054     \csname protected@edef\endcsname\x\endgroup
1055     \noexpand\section{String #1: #2}%
1056   }%
1057   \x
1058   \TestDriver{so}{#1}{#2}{#3}%
1059   \TestDriver{caps}{#1}{#2}{#3}%
1060   \TestDriver{ul}{#1}{#2}{#3}%

```

```

1061 \TestDriver{st}{#1}{#2}{#3}%
1062 \TestDriver{hl}{#1}{#2}{#3}%
1063 \TestDriver{an}{#1}{#2}{#3}%
1064 \TestDriver{sy}{#1}{#2}{#3}%
1065 \TestDriver{soulH}{#1}{#2}{#3}%
1066 }
1067 \makeatother

```

3.2.3 Testing

```

1068 \begin{document}
1069 \Test A{}{}%
1070 \Test B{Hello World}{Hello World}%
1071 \Test C{%
1072   Umlauts: ^^c3^^84^^c3^^96^^c3^^9c^^c3^^a4^^c3^^b6^^c3^^bc^^c3^^9f%
1073 }{%
1074   Umlauts: \"A\"O\"U\"a\"o\"u\\ss
1075 }%
1076 \Test D{Euro: ^^e2^^82^^ac}{Euro: \texteuro}%
1077 \Test E{Stra^^c3^^9fe}{Stra\\ss e}%
1078 \Test F{R^^c3^^b6mer}{R\"omer}%
1079 \Test G{A^^e2^^80^^93B^^e2^^80^^94C}{A--B---C}%
1080 \Test H{X^^c2^^a0Y}{X-Y}%
1081 \Test I{A^^c5^^a4}{A\\v T}%
1082 \Test J{A,B,,C,,,D,,,E}{A,B,,C,,,D,,,E}%
1083 \Test K{A'B''C'''D''''E}{A'B''C'''D''''E}%
1084 \Test L{A`B``C``D````E}{A`B``C``D````E}%
1085 \Test M{A$x$B}{A$x$B}%
1086 \Test N{A\mbox{abc}B}{A\mbox{abc}B}%
1087 \Test O{,TA''}{,TA''}%
1088 \Test P{{!`}Hola{?`}}{!`}Hola{?`}}%
1089 \Test Q{re-sent\slash x}{re-sent\slash x}%
1090 \Test R{new\\line}{new\\line}%
1091 \Test S{foo\\linebreak bar}{foo\\linebreak bar}%
1092 \Test T{Virchow{sche}}{Virchow{sche}}%
1093 \Test U{A\soulomit{foo}B}{A\soulomit{foo}B}%
1094 \Test V{A\texttt{xyz}B}{A\texttt{xyz}B}%
1095 \Test W{ffi}{ffi}%
1096 \Test X{f{}f{}i}{f{}f{}i}%
1097 \Test Y{f\mbox{}}f\mbox{}i}{f\mbox{}f\mbox{}i}%
1098 \Test Z{\c{"a}}{\c{"a}}}%
1099 <*test2 j test3>
1100 \let\abcx\UNDEFINED
1101 \def\abc{%
1102   \begingroup
1103     \def\abcx{x}%
1104     \abcx
1105   \endgroup
1106 }%
1107 \Test{AA}{[{x\abc x}]}[{xxx}]}%
1108 </test2 j test3>
1109 \end{document}
1110 </test2 j test3 j test4 j test5>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

CTAN:macros/latex/contrib/oberdiek/soulutf8.dtx The source file.

¹[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

[CTAN:macros/latex/contrib/oberdiek/soulutf8.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for \TeX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain \TeX :

```
tex soulutf8.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>soulutf8.sty</code>	<code>→ tex/generic/oberdiek/soulutf8.sty</code>
<code>soulutf8.pdf</code>	<code>→ doc/latex/oberdiek/soulutf8.pdf</code>
<code>test/soulutf8-test1.tex</code>	<code>→ doc/latex/oberdiek/test/soulutf8-test1.tex</code>
<code>test/soulutf8-test2.tex</code>	<code>→ doc/latex/oberdiek/test/soulutf8-test2.tex</code>
<code>test/soulutf8-test3.tex</code>	<code>→ doc/latex/oberdiek/test/soulutf8-test3.tex</code>
<code>test/soulutf8-test4.tex</code>	<code>→ doc/latex/oberdiek/test/soulutf8-test4.tex</code>
<code>test/soulutf8-test5.tex</code>	<code>→ doc/latex/oberdiek/test/soulutf8-test5.tex</code>
<code>soulutf8.dtx</code>	<code>→ source/latex/oberdiek/soulutf8.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your \TeX distribution (`te \TeX` , `mik \TeX` , ...) relies on file name databases, you must refresh these. For example, `te \TeX` users run `texhash` or `mktextlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk soulutf8.pdf unpack_files output .
```

Unpacking with L^AT_EX. The .dtx chooses its action depending on the format:

plain T_EX: Run docstrip and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for docstrip (really, docstrip does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{soulutf8.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the .dtx or the .drv to generate the documentation. The process can be configured by the configuration file ltxdoc.cfg. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex soulutf8.dtx
makeindex -s gind.ist soulutf8.idx
pdflatex soulutf8.dtx
makeindex -s gind.ist soulutf8.idx
pdflatex soulutf8.dtx
```

5 Catalogue

The following XML file can be used as source for the [T_EX Catalogue](#). The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is soulutf8.xml.

```
1111 <*catalogue>
1112 <?xml version='1.0' encoding='us-ascii'?>
1113 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
1114 <entry datestamp='$Date$' modifier='$Author$' id='soulutf8'>
1115   <name>soulutf8</name>
1116   <caption>Permit use of UTF-8 characters in soul.</caption>
1117   <authorref id='auth:oberdiek'>/>
1118   <copyright owner='Heiko Oberdiek' year='2007'>/>
1119   <license type='lppl1.3'>/>
1120   <version number='1.0'>/>
1121   <description>
1122     This package extends package <xref refid='soul'>soul</xref> and adds
1123     some support for UTF-8. Namely the input encodings in
1124     &#x2018;<tt>utf8.def</tt>&#x2019; from package
1125     <xref refid='inputenc'>inputenc</xref> and
1126     &#x2018;<tt>utf8x.def</tt>&#x2019; from package
1127     <xref refid='unicode'>ucs</xref> are supported.
1128   <p/>
1129   The package is part of the <xref refid='oberdiek'>oberdiek</xref>
1130   bundle.
1131 </description>
1132 <documentation details='Package documentation'
1133   href='ctan:/macros/latex/contrib/oberdiek/soulutf8.pdf'>/>
1134 <ctan file='true' path='/macros/latex/contrib/oberdiek/soulutf8.dtx'>/>
1135 <miktex location='oberdiek'>/>
1136 <texlive location='oberdiek'>/>
1137 <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip'>/>
1138 </entry>
1139 </catalogue>
```


6 References

- [1] Melchior Franz: *The soul package*; 2003/11/17;
CTAN:macros/latex/contrib/soul/.
- [2] Dominique P. G. Unruh: *ucs.sty – Unicode Support*; 2004/10/17;
CTAN:macros/latex/contrib/unicode/.
- [3] Frank Mittelbach, Chris Rowley: *Providing some UTF-8 support via inputenc*;
2006/03/30;
CTAN:macros/latex/base/utf8ienc.dtx.

7 History

[2007/09/09 v1.0]

- First version.

8 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols		
\"	1074, 1078, 1098	\an 814
\#	656	\AtBeginDocument 809
\%	732	
\@	657, 730	B
\@PackageError	148	\baselineskip 973
\@PackageInfo	893, 898, 904, 911	\begin 897, 1068
\@PackageWarningNoLine	185	\bfseries 989
\@ehc	771	\body 674, 678
\@empty	899, 905, 912	\boxA 888, 902, 942, 943, 944,
\@firstofone	665, 668	945, 947, 950, 951, 952, 1003, 1004
\@gobble	504, 662, 670	\boxB 889, 909,
\@ifDefined	767, 776, 783, 784	942, 944, 945, 948, 951, 1004, 1014
\@ifdefinable	775	\boxC 890, 923, 943, 950, 952
\@ifundefined	768	\break 245, 265, 267, 330, 350, 352
\@latex@error	769	
\@ne	215, 217, 219,	C
221, 300, 302, 304, 306, 931, 1051		\c 1040, 1098
\@nil	404, 407, 429, 433	\catcode 2, 3, 5, 6, 7,
\@onelevel@sanitize	153, 381, 455, 471	8, 9, 10, 11, 12, 13, 33, 34, 36,
\@undefined	58, 129	37, 38, 39, 40, 41, 42, 43, 44, 45,
\\	242, 327, 731, 1029, 1090	46, 47, 48, 49, 69, 70, 72, 73, 74,
\{	654, 975	78, 79, 80, 81, 82, 83, 84, 87, 88,
\}	655, 974	90, 91, 92, 93, 97, 99, 169, 170,
\~	1047	172, 173, 654, 655, 656, 657,
		692, 701, 709, 713, 730, 731, 732
_	816	\cdot 838
		\char 816
A		\chardef 411, 438, 442, 446, 448
\abc	1036, 1101, 1107	\clearpage 1026
\abcx	1100, 1103, 1104	\copy 965, 1003, 1014
\active	121	\count@ 659,
\advance	215, 217, 219, 221, 300,	688, 692, 694, 695, 699, 701,
302, 304, 306, 695, 703, 718, 1051		702, 703, 707, 709, 712, 713,
\afterassignment	178	717, 718, 1044, 1046, 1047, 1051
\aftergroup	29	\countdef 659
		\csname 14, 21, 50,
		66, 76, 130, 153, 380, 381, 658,

661, 664, 667, 722, 749, 761, 770, 777, 778, 785, 786, 894, 1054	414, 416, 437, 441, 445, 456, 472, 478, 658, 661, 664, 667, 722
\CurrentOption 162	\immediate 23, 52
D	\IncludeTests 886
\DeclareOption 133, 138, 162	\input 141, 144, 152, 723
\DeclareRobustCommand	\iterate 675, 677, 679
..... 131, 136, 814, 825, 850	K
\DeclareUnicodeCharacter 804	\kern 838
\discretionary 834, 844	L
\documentclass 129, 756	\lccode 1047
\dp 941, 951, 952	\leavevmode 233, 318
E	\lefthyphenmin 828
\empty 17, 18	\linebreak 268, 270, 353, 355, 816, 818, 1028, 1091
\end 750, 953, 1109	\llap 974
\endcsname 14, 21, 50, 66, 76, 130, 153, 380, 381, 658, 661, 664, 667, 722, 749, 761, 770, 777, 778, 785, 786, 894, 1054	\LoadCommand 723, 733
\endinput 29, 128	\LogTests 887
\endlinechar 4, 35, 71, 77, 89	\loop 673, 689, 700, 708, 1045
\errmessage 711	\lowercase 1048
\etex@unexpanded	M
. 464, 486, 494, 576, 601, 626, 645	\makeatletter 766, 813, 1024
\Expect 932, 933, 934, 940, 941, 942, 943, 944, 950, 951, 952	\makeatother 790, 1067
G	\maxdimen 929, 930
\gdef 852, 880	\mbox 255, 340, 1003, 1014, 1033, 1086, 1097
H	\meaning 156, 402, 426
\hbox .. 257, 342, 588, 600, 601, 613, 625, 626, 838, 843, 900, 907, 921	\MessageBreak 186, 187, 188
\hfil 245, 330	N
\hfill 966, 1006, 1015	\NeedsTeXFormat 755
\hfuzz 958	\newcommand ... 132, 137, 767, 774, 782, 878, 891, 955, 962, 1000, 1025
\hsize 957	\newsavebox 888, 889, 890
\HstringA 901, 932, 933	\next 679, 681, 683
\HstringB 908, 932	\nobreak 245, 250, 330, 335, 459
\HstringC 922, 933	\nobreakspace 804
\ht 940, 944, 945, 950, 1004	\noindent 964, 1002, 1013
I	\null 230, 236, 244, 249, 315, 321, 329, 334, 458
\if 197, 234, 282, 319	\number 714
\ifcase 362, 365, 507, 515, 524, 532, 541, 549	O
\ifcat 271, 273, 356, 358	\origshow 807, 810
\ifdim 935, 945, 969, 970, 1004	P
\ifetex@unexpanded 168	\PackageError 134, 139, 148
\ifnum 201, 203, 205, 207, 286, 288, 290, 292, 694, 702, 709, 717, 972, 980, 1046	\PackageInfo 26
\ifSOUL@ignorespaces 237, 322	\par 232, 233, 317, 318, 963, 998, 1001, 1012, 1022
\ifx 15, 18, 21, 50, 58, 61, 129, 130, 153, 182, 210, 211, 212, 213, 214, 216, 218, 220, 227, 232, 242, 247, 251, 255, 257, 259, 265, 268, 295, 296, 297, 298, 299, 301, 303, 305, 312, 317, 327, 332, 336, 340, 342, 344, 350, 353, 412,	\PassOptionsToPackage 162
	\phantom 976, 982, 991, 996, 1010, 1019
	\ProcessOptions 163
	\protect .. 559, 571, 584, 596, 609, 621
	\ProvidesPackage 19, 67
	Q
	\qqquad 977, 983, 993
	R
	\raisebox 973

\RangeCatcodeCheck	266, 269, 314, 320, 328, 333, 337, 346, 351, 354, 457, 473, 479
. 706, 734, 735, 736, 737, 738, 739, 740, 741, 742, 743, 744, 745	
\RangeCatcodeInvalid	698, 726, 727, 728, 729
\repeat ..	673, 685, 696, 704, 719, 1052
\RequirePackage	164, 165, 166
\RestoreCatcodes ..	687, 690, 691, 746
\RestoreOrg	782, 906, 913, 914, 915, 916, 917, 918, 919, 920
\righthyphenmin	829
\rlap ...	975, 981, 990, 995, 1009, 1018
S	
\SavedUnexpanded	753, 801
\SaveOrg	774, 791, 792, 793, 794, 795, 796, 797, 798, 799
\section	1055
\setbox	900, 907, 921, 956
\SetTestVBox	902, 909, 923, <u>955</u>
\show	807, 810
\showbox	937, 938, 947, 948
\showboxbreadth	930
\showboxdepth	929
\slash	251, 336, 1089
\small	968, 1008, 1017
\SOUL@	823, 848, 876
\SOUL@@	197, 210, 211, 212, 213, 214, 216, 218, 220, 227, 232, 234, 242, 247, 251, 255, 257, 259, 265, 268, 271, 273, 282, 295, 296, 297, 298, 299, 301, 303, 305, 312, 317, 319, 327, 332, 336, 340, 342, 344, 350, 353, 356, 358, 402, 426
\SOuL@addfouroctets	373, <u>492</u>
\SOUL@addgroup	272, 357, <u>557</u>
\SOUL@addmath	274, 359, <u>582</u>
\SOUL@addprotect	256, 258, 341, 343, <u>607</u>
\SOuL@addthreecoctets	371, <u>469</u>
\SOUL@addtoken	463, 464, 485, 486, 493, 494, <u>632</u>
\SOuL@addtwooctets	369, <u>453</u>
\SOuL@analyzeutfviii	361, <u>398</u>
\SOuL@analyzeutfviiix	363, <u>422</u>
\SOUL@apo	205, 219, 290, 304, 524, 530, 532, 538
\SOuL@AtEnd	95, 96, 128, 651
\SOuL@charhash	394, 427, 432
\SOUL@charkern	845
\SOuL@charthree	396, 441
\SOuL@chartwo	395, 445
\SOuL@checkutfviii	401, 406
\SOuL@checkutfviiix	425, <u>431</u>
\SOuL@cmd	177, 182, 184, 193
\SOuL@cmdcheck	178, <u>181</u>
\SOUL@comma	203, 217, 288, 302, 507, 513, 515, 521
\SOuL@defsanitizedstring	379, 383, 384, 385, 386, 387, 388, 389, 390
\SOUL@dotoken	276, 366
\SOUL@doword	229, 235, 243, 248, 252, 261,
\SOuL@empty	397, 437
\SOUL@error	<u>144</u>
\SOUL@eval	<u>195</u>
\SOUL@eventuallyexhyphen	230, 236, 244, 249, 253, 315, 321, 329, 334, 338, 458, 474, 480
\SOUL@everyexhyphen ...	819, 841, 864
\SOUL@everyhyphen	818, 833, 861
\SOUL@everylowerthan	822, 873
\SOUL@everyspace	239, 245, 250, 270, 324, 330, 335, 355, 459, 816, 831, 855
\SOUL@everysyllable ...	820, 832, 867
\SOUL@everytoken	821, 870
\SOUL@exhyphen	254, 339, 475, 481
\SOUL@flushapo	206, 212, 225, 291, 297, 310, <u>523</u>
\SOUL@flushcomma	204, 211, 224, 289, 296, 309, <u>506</u>
\SOUL@flushgrave	208, 213, 226, 293, 298, 311, <u>540</u>
\SOUL@flushminus	202, 210, 223, 287, 295, 308
\SOUL@grave	207, 221, 292, 306, 541, 547, 549, 555
\SOUL@hyphkern	835, 842
\SOUL@ignorespacesfalse	199, 284
\SOUL@ignorepacestrue	246, 331
\SOUL@minus	201, 215, 286, 300
\SOUL@on	196, 228, 233, 241, 256, 258, 260, 272, 274, 276, 279, 281, 313, 318, 326, 341, 343, 345, 357, 359, 366, 369, 371, 373, 377
\SOuL@next	460, 462, 467, 476, 482, 484, 490
\SOuL@octets	362, 365, 411, 438, 442, 446, 448
\SOuL@orgDeclareOption	133, 138
\SOuL@orgDeclareRobustCommand ...	131, 136
\SOuL@orgnewcommand	132, 137
\SOuL@orgPackageError	134, 139
\SOuL@orgSOUL@error	145, 149
\SOUL@postamble	817, 858
\SOUL@preamble	815, 827, 851
\SOuL@redefine	<u>175</u> , 195, 496, 506, 523, 540, 557, 582, 607, 632
\SOuL@remainingtoken	501, <u>503</u>
\SOuL@restorelatexcmds	135, 142
\SOUL@scan	196, 233, 241, 263, 281, 318, 326, 348, 460, 476, 482, 568, 580, 593, 605, 618, 630, 640, 649
\SOUL@sethyphenchar	836
\SOUL@setkern	835, 842, 845
\SOUL@setup	826
\SOUL@spaceskip	262, 347
\SOUL@spc	197, 234, 282, 319
\SOUL@splittoken	<u>496</u>
\SOUL@stop	227, 312, 496, 503

<code>\SOuL@stringcsnameu</code>	428, 433	<code>\textbackslash</code>	1028,
<code>\SOuL@stringemdash</code>	392, 478		1029, 1031, 1034, 1036, 1038, 1041
<code>\SOuL@stringendash</code>	391, 472	<code>\textbraceleft</code>	1031, 1034, 1038, 1041
<code>\SOuL@stringfour</code>	416	<code>\textbraceright</code>	1031, 1034, 1038, 1041
<code>\SOuL@stringmacrocolon</code>	427, 432	<code>\texteuro</code>	1076
<code>\SOuL@stringnobreakspace</code>	393, 456	<code>\texttt</code>	816, 1037, 1094
<code>\SOuL@stringoctets</code>	403, 407	<code>\the</code>	77, 78, 79, 80, 81, 82, 83, 84,
<code>\SOuL@stringthree</code>	414		97, 509, 511, 517, 519, 526, 528,
<code>\SOuL@stringtwo</code>	412		534, 536, 543, 545, 551, 553,
<code>\SOuL@stringundeferr</code>	428, 433		562, 574, 587, 599, 612, 624,
<code>\SOuL@stringUTFviii</code>	403, 407		635, 644, 692, 712, 713, 821,
<code>\SOuL@syllable</code>	832		832, 934, 940, 941, 942, 943,
<code>\SOuL@temp</code>	179, 182, 184,		944, 950, 951, 952, 975, 981, 990
	186, 189, 410, 412, 414, 416,	<code>\thr@@</code>	201, 286, 415, 446
	436, 437, 440, 441, 444, 445,	<code>\TMP@EnsureCode</code>	94, 101, 102,
	454, 455, 456, 470, 471, 472, 478		103, 104, 105, 106, 107, 108,
<code>\SOUL@token</code>	497, 500, 821		109, 110, 111, 112, 113, 114,
<code>\SOUL@word</code>	498, 504, 509, 511, 517,		115, 116, 117, 118, 119, 120,
	519, 526, 528, 534, 536, 543,		121, 122, 123, 124, 125, 126, 127
	545, 551, 553, 561, 562, 573,	<code>\tracingonline</code>	931
	574, 586, 587, 598, 599, 611,	<code>\tw@</code>	203, 205, 207, 288, 290, 292, 413, 448
	612, 623, 624, 634, 635, 643, 644		
<code>\SOULH</code>	852		U
<code>\soulH</code>	850	<code>\UNDEFINED</code>	754, 1100
<code>\soulHadd</code>	853, 856,	<code>\unexpanded</code>	753, 754, 801
	859, 862, 865, 868, 871, 874, 878	<code>\unskip</code>	245, 330
<code>\soulHstring</code>	880,	<code>\usepackage</code>	757, 758, 759, 760, 762,
	881, 899, 901, 905, 908, 912, 922		763, 764, 765, 800, 803, 808, 885
<code>\soulomit</code>	259, 260, 344, 345, 1030, 1093		V
<code>\space</code>	712, 713, 721, 831, 975, 1003, 1014	<code>\v</code>	1081
<code>\spaceskip</code>	262, 347	<code>\vbox</code>	956
<code>\ss</code>	1074, 1077	<code>\vrule</code>	1003, 1014
<code>\strip@prefix</code>	156, 159		W
<code>\subsection</code>	892	<code>\wd</code>	934, 935,
<code>\sy</code>	825		942, 943, 969, 970, 975, 981, 990
		<code>\write</code>	23, 52
	T		
<code>\Test</code>	725, 748, 1024, 1069,		X
	1070, 1071, 1076, 1077, 1078,	<code>\x</code>	14, 15, 18, 22, 26, 28,
	1079, 1080, 1081, 1082, 1083,		51, 56, 66, 75, 87, 399, 409, 423,
	1084, 1085, 1086, 1087, 1088,		435, 509, 511, 517, 519, 526,
	1089, 1090, 1091, 1092, 1093,		528, 534, 536, 543, 545, 551,
	1094, 1095, 1096, 1097, 1098, 1107		553, 560, 566, 572, 579, 585,
<code>\TestDriver</code>	891, 1058, 1059,		591, 597, 604, 610, 616, 622,
	1060, 1061, 1062, 1063, 1064, 1065		629, 633, 639, 642, 648, 1054, 1057
<code>\testdriver</code>	894, 900, 907, 921, 959		Z
<code>\TestInfo</code>	925, 926, 927, 962	<code>\z@</code>	419, 438, 513,
<code>\TestInfoVBox</code>	928, 1000		521, 530, 538, 547, 555, 828, 829
<code>\teststringA</code>	895, 900, 902		
<code>\teststringB</code>	896, 907, 909, 921, 923		